

Uniclass L331	EPIC C311
CI/SfB	Yq4

October 2006

# PA Grout

## Product Datasheet

## EuroMix Dry Mortar System

### 1. Identification

#### 1.1 Introduction

EuroMix PA Grout is ideal for Foundations and structural infill, designed to be used in pumps or where placement is restricted.

It is delivered in Silos or Pre-packed 25kg Bags.

#### 1.2 Authority

The individual components of this product comply with the requirements of BS/IS EN 206-1: 2002 and are manufactured under a BSI/NSAI registered ISO 9001 Quality System.

Materials used comply with the following standards:

Sand	BS EN 13139: 2002
Cement	BS EN 197-1: 2000 (UK) IS EN 197-1: 2000 (Ireland)
Aggregate	BS EN 12620: 2002

Admixtures do not contain calcium chlorides. Water added on site should be clean and free from impurities.

#### 1.3 General Advantages

- Fine aggregate
- Consistent mix proportions
- Pump application
- Guaranteed strengths
- Minimum wastage, maximum output

#### 1.4 Products

EuroMix PA Grout is also available in the following versions for specialist applications. Non Shrink, Super Strength, Fibre Reinforced, Underwater Grout, Micro Steel Reinforced. Please contact us for any applications not listed here on this datasheet.

### 2. Description

#### 2.1 Manufacture

Raw materials and end products are subject to regular quality control procedures and testing.

Dried sand and other materials are weighed and mixed under computer control with rigorous quality assurance procedures.

#### 2.2 Compressive strength classes

EuroMix PA Grout can be supplied in strength classes to suit the requirements of the specifier complying with BS EN 206-1 as set out in the table below:

##### Characteristic Strength N/mm<sup>2</sup>

Strength Class	C24/30	C28/35	C32/40
Cylinder	24	28	32
Cube	30	35	40

#### 2.3 Colours

Natural grey

### 3. Performance

CPI EuroMix PA Grout is specially designed to give excellent workability when wet, and to harden to a durable finish.

#### 3.1 Water Addition

CPI EuroMix PA Grouts in 25kg bags should be mixed with the approximate water addition rates per bag as detailed below, Water should be clean and free from impurities.

25kg Bag Addition rates:

PA 30 - 3.50 Ltrs
PA 35 - 3.75 Ltrs
PA 40 - 4.0 Ltrs

When PA Grout is being supplied by the CPI EuroMix Silo please contact your local representative for advice on Flow meter settings.

## 4. Sitework

The enhanced flexibility of the dry mortar system offers several options on site:

- Direct discharge into a skip or mobile pump
- Transfer of dry material to a remote mixing station

When a silo is used, it should be placed on a firm level base measuring at least 3m x 3m. It is delivered complete with all necessary mixing equipment, which can be used by any site operative once a EuroMix Service Technician has given them basic training.

After connecting power and water supplies, the system is ready for use. Once the water flow rate is adjusted to give concrete of the required workability, it is simply a question of push-button operation to produce consistently high quality concrete whenever it is needed.

## 5. Prices and Conditions of Sale

Our Sales Office will be pleased to provide quotations for specific projects. All quotations are subject to our Conditions of Sale – a copy of which is available on request.

## 6. Supply

EuroMix PA Grout is available throughout the market area of each plant.

Silos are delivered with up to 16 tonnes of dry mortar and may be refilled by bulk tanker.

EuroMix PA Grout may also be delivered in minisilos or pre-packed 25kg bags.

## 7. Health & Safety

For health and safety information – see Material Safety Datasheet.

## 8. Technical Services

Fully trained Service Technicians are available at all times to provide on-site support to users of the EuroMix Dry Mortar System. Our Technical Advisory Service is available to give expert advice on the specification or use of EuroMix PA Grout.

### Beaconsfield

Springfield Farm Quarry, Broad Lane, Beaconsfield, Buckinghamshire HP9 1XD  
Tel: +44 (0) 1494 730 134  
Fax: +44 (0) 1494 730 816

### Bilston, Wolverhampton

Springvale Industrial Estate, Springvale Avenue Bilston, Wolverhampton  
West Midlands WV14 0QL  
Tel: +44 (0) 1902 357 500  
Fax: +44 (0) 1902 357 501

### Coatbridge

Gartsherrie Industrial Estate, Hornock Rd, Coatbridge ML5 2DX  
Tel: +44 (0) 1236 700 500  
Fax: +44 (0) 1236 449 850

### Dublin

Laraghcon, Lucan, Co. Dublin  
Tel: +353 (1) 630 2700  
Fax: +353 (1) 628 0331

### Harlow

29 Mead Industrial Park Riverway, Harlow Essex CM20 2SE  
Tel: +44 (0) 1279 634 680  
Fax: +44 (0) 1279 634 687

### Irlam, Manchester

Northbank Industrial Estate Martens Road, Irlam Manchester M44 5AX  
Tel: +44 (0) 161 777 7500  
Fax: +44 (0) 161 777 7501

### Leeds

Stadium Park, Altofts Lane, Whitwood Castleford, WF10 5PZ  
Tel: +44 (0) 1977 523 300  
Fax: +44 (0) 1977 523 333

### Northfleet

Robins Wharf, Grove Road, Northfleet, Kent DA11 9AX  
Tel: +44 (0) 1474 331 555  
Fax: +44 (0) 1474 325 080

### Southampton

Marchwood Industrial Park Marchwood, Southampton Hants SO40 4PB  
Tel: +44 (0) 2380 662 000  
Fax: +44 (0) 2380 662 009

### Bristol

Unit 8, Sevenside Industrial Park, Central Avenue, Bristol BS10 7SD  
Tel: +44 (0) 1179 160 300  
Fax: +44 (0) 1179 160 311



Helpline: **0845 850 9090 (UK) 01 630 2700 (Ireland)**

Visit us at: **[www.euromix.com](http://www.euromix.com)**

E-mail: **[info@cpieuromix.com](mailto:info@cpieuromix.com)**

